



Sustainable Technologies



Solar Remediation



SPECIFICATIONS

VARISUN Solar Vapor Extraction Systems	VS-VE03	VS-VE05	VS-VE7.5	VS-VE10
Rated Power, KW	2.7	5.40	6.75	8.1
MAX Pump HP rating	3	5	7.5	10
Voltage , 3 Phase VAC	240	240	240	230/480
Max Flow Max Vacuum	70 cfm, 50" H2O	200cfm, 100" H2O	300cfm, 135" H2O	400 cfm, 150" H2O
Total Footprint, FT	11' x 12'	23' x 12'	33' x 12	44' x 12'
Number of pods	1	2	2 or 3	4
VARISUN Direct Solar Air Sparge Systems	VS-AS03	VS-AS05	VS-AS7.5	VS-AS10
Rated Power, KW	2.7	5.40	6.75	8.1
MAX Pump HP rating	3	6.00	7.5	10
Voltage , 3 Phase VAC	230	230	240	230-480
Max Flow Max Pressure	30 cfm 12 psi	40 cfm 12 psi	70 cfm 10 psi	370 cfm 22 psi
Footprint, FT	11' x 12'	11' x 12'	33' x 12	11' x 12'
Number of Pods	1	2	2 or 3	3