



SPECIFICATIONS

	VARISUN Solar Vapor Extraction Systems				
	Low Vacuum	VS-VE03	VS-VE05	VS-VE7.5	VS-VE10
Rated Power, KW		2.5	5.9	8.85	11.8
MAX Pump HP rating		5	7.5	10	10
Voltage , 3 Phase VAC		240	240	240	230/480
Max Flow Regen Blower Max Vacuum		200cfm, 100" H2O	300cfm, 135" H2O	400 cfm, 150" H2O	400 cfm, 150" H2O
Total Footprint, FT		11' x 12'	23' x 12'	33' x 12'	44' x 12'
Number of pods		1	2	2 or 3	4
	VARISUN Direct Solar Air Sparge Systems	VS-AS03	VS-AS06	VS-AS09	VS-AS12
Rated Power, KW		2.95	5.7	8.85	11.8
MAX Pump HP rating		4.6	7.1	11.5	10
Voltage , 3 Phase VAC		230	230	240	230-480
Max Flow Max Pressure		30 cfm 12 psi	57 cfm 31 psi	103 cfm 19 psi	000 cfm 31 psi
Footprint, FT		11' x 12'	11' x 12'	33' x 12'	11' x 12'
Number of Pods		1	2	2 or 3	3